

**Messuhr digital** **Digital dial indicator**

- Werksnorm
- mit großer LCD-Anzeige
- Einspannschaft Ø 8 mm
- Batterie SR44
- inkl. Etui

- factory standard
- with big LCD display
- stem Ø 8 mm
- battery SR44
- incl. box



280-56



280-57



280-58

Funktionen: Ein/Aus, Null, Hold, mm/inch  
 Features: on/off, zero, hold, mm/inch

> mm <	mm	inch	mm	mm	No.
12,7	0,01	0,0005	56,3	0,03	280-56
25,4	0,01	0,0005	56,3	0,03	280-57
50,8	0,01	0,0005	56,3	0,03	280-58
12,7	0,001	0,00005	56,3	0,005	280-59

**Messuhr digital** **Digital dial indicator**

- Werksnorm
- mit großer LCD-Anzeige
- Einspannschaft Ø 8 mm
- Batterie CR2032
- inkl. Etui

- factory standard
- with large LCD readout
- stem Ø 8 mm
- battery CR2032
- incl. box

**280-40**

Funktionen: Ein/Aus, Null, mm/inch  
 Features: on/off, zero, mm/inch

**280-45 / 280-46**

Funktionen: Ein/Aus, Null, mm/inch, absolut, Toleranz  
 Features: on/off, zero, mm/inch, absolute, tolerance

> mm <	mm	inch	mm	mm	No.
12,5	0,01	0,0005	56	0,03	280-40
12,5	0,01	0,0005	56	0,03	280-45
25	0,01	0,0005	56	0,03	280-46



280-40



280-45

> mm <	Messbereich	Range
	Ablesung	Reading
	Gehäusedurchmesser	Outside diameter
	Genauigkeit	Accuracy