

eco-fix · eco-fix^{plus}

	APPLICATION	PRODUCT LINES																
<p>Part No.: K551047 Weight 9 g</p> <p>M6 Slot nut h = 15 mm eco-fix Use with Type B receiver brackets for 20mm location pins, for mounting e.g., location pins on the receiving bracket, to reach any position in space, e.g., for positioning of clamping elements directly on receiving points.</p>	 <table><tr><th>Part No.:</th><th colspan="3">Compatible receiver brackets</th></tr><tr><td>K551045</td><td>Receiving bracket eco-fix</td><td>L = 120 mm</td><td>Type B</td></tr><tr><td>K551247</td><td>Receiver bracket eco-fix^{plus}</td><td>L = 120 mm</td><td>Type B</td></tr><tr><td>K551248</td><td>Receiver bracket eco-fix^{plus}</td><td>L = 170 mm</td><td>Type B</td></tr></table>	Part No.:	Compatible receiver brackets			K551045	Receiving bracket eco-fix	L = 120 mm	Type B	K551247	Receiver bracket eco-fix ^{plus}	L = 120 mm	Type B	K551248	Receiver bracket eco-fix ^{plus}	L = 170 mm	Type B	 <p>eco-fix eco-fix^{plus}</p>
Part No.:	Compatible receiver brackets																	
K551045	Receiving bracket eco-fix	L = 120 mm	Type B															
K551247	Receiver bracket eco-fix ^{plus}	L = 120 mm	Type B															
K551248	Receiver bracket eco-fix ^{plus}	L = 170 mm	Type B															
<p>Part No.: K551227 Weight 14 g</p> <p>Receiving bracket M6 To reach any receiving position between the connecting threads.</p>		 <p>eco-fix</p>																
<p>Location pin Ø 20 mm For the adjustment of the required height of the fixture</p> <table><tr><th>Part No.:</th><th>L mm</th><th>weight g</th></tr><tr><td>K551028</td><td>13</td><td>10</td></tr><tr><td>K551029</td><td>25</td><td>19</td></tr><tr><td>K551030</td><td>50</td><td>39</td></tr><tr><td>K551031</td><td>100</td><td>83</td></tr></table>	Part No.:	L mm	weight g	K551028	13	10	K551029	25	19	K551030	50	39	K551031	100	83		 <p>eco-fix</p>	
Part No.:	L mm	weight g																
K551028	13	10																
K551029	25	19																
K551030	50	39																
K551031	100	83																
<p>Part No.: K551043 L = 25mm Weight 19 g</p> <p>Location pin Ø 20 mm With bore Ø 8 mm for connecting of elements with 6 mm connecting pin.</p>		 <p>eco-fix</p>																
<p>Part No.: K551040 Weight 44 g</p> <p>Adjustable location pin Ø 20 mm For the adjustment of the required height of receiving positions.</p>		 <p>eco-fix</p>																