

# DOTEKY M5

## Prodloužení z uhlíkových vláken

konec z titanu

lepší pevnost v ohybu a krutu  
teplotně odolný



Obj.č.	Analogicky Renishaw	S mm	L mm	ML mm	ML1 mm	D mm	DS mm	DS1 mm	Váha g
K656023	A-5555-0647		40			11			7,6
K656024	A-5555-0648		50			11			8,3
K656025	A-5555-0649		60			11			9
K656026	A-5555-0623		70			11			9,7
K656027	A-5555-0650		80			11			10,4
K656028	A-5555-0651		90			11			11,1
K656029	A-5555-0652		100			11			11,8
K656030	A-5555-0425		120			11			13,2
K656031	A-5555-0424		150			11			15,4
K656032	A-5555-0K653		180			11			17,5
K656033	A-5555-0654		200			11			18,9
K656034	A-5555-0655		250			11			22,4
K656035	A-5555-0642		300			11			25,9
K656036	A-5555-0656		400			11			33,0
K656037	A-5555-0620		40			20			23,8
K656038	A-5555-0657		50			20			25,1
K656039	A-5555-0658		60			20			26,5
K656040	A-5555-0621		80			20			29,3
K656041	A-5555-0659		100			20			32,1
K656042	A-5555-0660		120			20			34,9
K656043	A-5555-0661		150			20			39,0
K656044	A-5555-0662		180			20			43,2
K656045	A-5555-0663		200			20			46,0
K656046	A-5555-0427		250			20			52,9
K656047	A-5555-0664		300			20			59,9
K656048	A-5555-0665		400			20			73,8
K656049	A-5555-0667		500			20			87,7
K656050	A-5555-0668		600			20			101,5