

Service MANOSKOP® torque wrench w.mount for insert tools

730 Fix



Art.No. **96503040**
GTIN **4018754269471**
Model **730/40 FIX**

Label.

Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 80-400N·m Inside square stitch size 14 x 18 mm L. 607mm

Features.

- For work in serial production
- Adjustment knob can be unscrewed after setting the trigger torque - unintentional changing of the setpoint torque is thus prevented
- The included TORX® TAMPER-RESISTANT fuse screw also protects against tampering as well as the included adhesive seals No adjustment possible without breaking the seal
- Triggering
- No reset to "0" required, since measuring element is only loaded during the tightening process
- Mount for interchangeable bits/sockets
- QuickRelease safety lock
- Fast, precise adjustment with QuickSelect quick adjustment
- Dual stop signal
- Easy to read double scale with colour differentiation of N·m/ft·lb and ft·lb/in·lb respectively
- Counter-clockwise tightening by turning the bits/sockets
- Continued loading after triggering or loading against the operating direction, e.g. with screws that are stuck, does not affect the triggering mechanism, which is therefore protected from damage.
- 2-component handle with hand-friendly green soft zone (resistant to oils, greases, fuels, brake fluids and Skydrol)
- Calibration with perfectControl® calibration system No. 7794 or calibration device No. 7706. Where applicable Readjustment does not require disassembly
- Certificate in accordance with DIN EN ISO 6789-2:2017
- DBGM
- In a sturdy plastic box (size 80-100 in sturdy steel box)
- **Display deviation ± 3%**

Advantages.

For work in serial production

Product highlights.



Flexible rod principle.

Mechanical torque wrenches from STAHLWILLE have a wear-resistant trigger system with a flexible rod. In contrast to conventional torque wrenches with spiral springs, the STAHLWILLE system eliminates one key work step: once the fastener has been tightened, it is not necessary to reset the wrench to »0«.



Simple.

Quick adjustment from outside, no disassembly of the torque wrench required, with two adjustment points for the maximum & minimum values.



Clear view.

Easy-to-read dual scale with colour differentiation between the N·m and ft.lb scales to simplify fine setting.


Technologies and features.



Value Lock (tamper resistant)

Adjustment knob can be unscrewed after setting the release torque. This prevents unintentional changing of the set torque. The supplied TORX® TAMPERRESISTENT locking screw also protects against tampering. The same applies to the enclosed adhesive seals. No adjustment possible without breaking the seal.

Technical Drawing.



Technical Attributes.

Width mm (b)	28 mm
Fine scale division	2 N·m

Logistics data.

Length (IFS)	685
Width (IFS)	95

Weight with box	2444 g	Height (IFS)	70
Size	40	Length (packed, mm)	685
Size hexagon socket [internal square]	14 x 18 mm	Width (packed, mm)	95
Height mm (h)	23 mm	Height (packed, mm)	70
Length mm (L)	607 mm	Volume (packed, mm)	4.55525 dm ³
LF	564,5 mm	Artikelnummer	96503040
Lowest value of measurement range N·m	80 N·m	Weight (gross, kg)	2,430
Measuring range ft·lb	60-300 ft·lb	Weight PAP (kg)	0,130
Measuring range N·m	80-400 N·m	Weight PVC (kg)	0,000
Nominal value N·m	400 N·m	GTIN	4018754269471
SF	25 mm	Country of origin	GERMANY
Scale division [E1]	20 N·m	Region of origin	Nordrhein-Westfalen
Scale division [E2]	10 ft·lb	WEEE/Electrical Act	nicht ear-pflichtig
		Customs tariff no.	82041100
		Numbers of content units per order units	1
		Weight	1666 g

Parts list.



50183040
Torque wrench service
MANOSKOP



81370003
Plastic case, empty



83071002
Inlay for plastic case



08160030
Bit screwdriver



19060001
Spare part

Variants.

Artikelnummer	Article number (ERP)	Article description (Autom._)	GTIN
96503005	730/5 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 10-50N·m Inside square stitch size 9 x 12 mm L. 330mm	4018754269433

96503010	730/10 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 20-100N·m Inside square stitch size 9 x 12 mm L. 386mm	4018754269440
96503012	730/12 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 25-130N·m Inside square stitch size 14 x 18 mm L. 421mm	4018754269457
96503020	730/20 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 40-200N·m Inside square stitch size 14 x 18 mm L. 467mm	4018754269464
96503040	730/40 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 80-400N·m Inside square stitch size 14 x 18 mm L. 607mm	4018754269471
96503065	730/65 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 130-650N·m Inside square stitch size 14 x 18 mm L. 890mm	4018754269655
96503465	730NII/65 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 130-650N·m Inside square stitch size 22 x 28 mm L. 911mm	4018754269778
96503080	730/80 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 160-800N·m Inside square stitch size 22 x 28 mm L. 1178mm	4018754269662
96503100	730/100 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 200-1000N·m Inside square stitch size 22 x 28 mm L. 1363mm	4018754269679
96583005	730A/5 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 90-450in lb Inside square stitch size 9 x 12 mm L. 330mm	4018754269785
96583010	730A/10 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 180-900in lb Inside square stitch size 9 x 12 mm L. 386mm	4018754269792
96583020	730A/20 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 350-1800in lb Inside square stitch size 14 x 18 mm L. 467mm	4018754269808
96583040	730A/40 FIX	Service MANOSKOP torque wrench w.mount for insert tools No. 730 Fix Measuring-R. 800-3600in lb Inside square stitch size 14 x 18 mm L. 607mm	4018754269815

GTIN-Code.



STAHLWILLE Eduard Wille GmbH & Co. KG

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0 · Fax: +49 202 4791-200
info@stahlwille.de · www.stahlwille.com · Copyright by STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal
Copyright by STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal