

SERVICE-MANOSKOP® torque wrench

730R



Art.No. **96504005**
GTIN **4018754269488**
Model **730R/5 QUICK**

Label.

SERVICE-MANOSKOP torque wrench No. 730R Measuring-R. 6-50N·m Output 3/8" L. 380mm

Features.

- triggering
- No reset to "0" necessary, as measuring element is only loaded during the tightening process
- receptacle for interchangeable plug-in tools
- QuickRelease safety lock
- Flash adjustment by easy-to-operate clamping lever in the handle
- ergonomically shaped, non-slip adjustment element with thumb recess
- optimised ball handle for fatigue-free working
- double stop signal
- double scale N·m/ft·lb or N·m/in·lb
- on request also available as N·m version only without double scale
- Left-hand tightening by turning over the plug-in tools
- Further loads after triggering or loads against the functional direction, e.g. with stuck screws, do not affect the triggering mechanism, which is thus protected against damage
- Calibration with the perfectControl® calibration device no. 7794 or the calibration system no. 7706. If necessary, readjustment without disassembly
- Certificate according to DIN EN ISO 6789-2:2017
- Display deviation $\pm 4\%$

Advantages.

6-50 N·m

Product highlights.



Flexible rod principle.

Mechanical torque wrenches from STAHLWILLE have a wear-resistant trigger system with a flexible rod. In contrast to conventional torque wrenches with spiral springs, the STAHLWILLE system eliminates one key work step: once the fastener has been tightened, it is not necessary to reset the wrench to »0«.



Wear-resistant.

Wear resistant trigger system with a flexible rod. In contrast to conventional torque wrenches, it is not necessary to reset the wrench to zero after each job to unload the spring. In this way, users benefit from long-term accuracy and safe measurement results with less time required.



Fast.

Rapid setting thanks to the easy-action locking lever in the handle. Ergonomically designed, non-slip adjuster with a thumb recess for fast, safe setting of the slider.



Simple.

Quick adjustment from outside, no disassembly of the torque wrench required, with two adjustment points for the maximum & minimum values.

Technical Attributes.

Output square drive outside (inch)	3/8"
Width mm (b)	50 mm
Height mm (h)	50 mm
Length mm (L)	380 mm
Measuring range ft·lb	5-36 ft·lb
Measuring range N·m	6-50 N·m
Scale division [E1]	2 N·m
Scale division [E2]	1 ft·lb

Logistics data.

Length (IFS)	380
Width (IFS)	50
Height (IFS)	50
Length (packed, mm)	380
Width (packed, mm)	50
Height (packed, mm)	50
Volume (packed, mm)	0.95 dm ³
Artikelnummer	96504005
Weight (gross, kg)	0,994
Weight PAP (kg)	0,000
Weight PVC (kg)	0,068
GTIN	4018754269488
Country of origin	GERMANY
Region of origin	Nordrhein-Westfalen
WEEE/Electrical Act	nicht ear-pflichtig
Customs tariff no.	82041100
Numbers of content units per order units	1

GTIN-Code.



Images.



STAHLWILLE Eduard Wille GmbH & Co. KG

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0 · Fax: +49 202 4791-200
info@stahlwille.de · www.stahlwille.com · Copyright by STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal
Copyright by STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal