

Torque spanner MANOSKOP®

730R



Art.No. **96504010**
GTIN **4018754269495**
Model **730R/10 QUICK**

Label.

Torque spanner MANOSKOP No. 730R Measuring-R. 20-100N·m Output 1/2" L. 430mm

Features.

- triggering
- No reset to "0" necessary, as measuring element is only loaded during the tightening process
- receptacle for interchangeable plug-in tools
- QuickRelease safety lock
- Flash adjustment by easy-to-operate clamping lever in the handle
- ergonomically shaped, non-slip adjustment element with thumb recess
- optimised ball handle for fatigue-free working
- double stop signal
- double scale N·m/ft·lb or N·m/in·lb
- on request also available as N·m version only without double scale
- Left-hand tightening by turning over the plug-in tools
- Further loads after triggering or loads against the functional direction, e.g. with stuck screws, do not affect the triggering mechanism, which is thus protected against damage
- Calibration with the perfectControl® calibration device no. 7794 or the calibration system no. 7706. If necessary, readjustment without disassembly
- Certificate according to DIN EN ISO 6789-2:2017
- Display deviation $\pm 4\%$

Advantages.

Releasing

Product highlights.



Flexible rod principle.

Mechanical torque wrenches from STAHLWILLE have a wear-resistant trigger system with a flexible rod. In contrast to conventional torque wrenches with spiral springs, the STAHLWILLE system eliminates one key work step: once the fastener has been tightened, it is not necessary to reset the wrench to »0«.



Wear-resistant.

Wear resistant trigger system with a flexible rod. In contrast to conventional torque wrenches, it is not necessary to reset the wrench to zero after each job to unload the spring. In this way, users benefit from long-term accuracy and safe measurement results with less time required.



Fast.

Rapid setting thanks to the easy-action locking lever in the handle. Ergonomically designed, non-slip adjuster with a thumb recess for fast, safe setting of the slider.



Simple.

Quick adjustment from outside, no disassembly of the torque wrench required, with two adjustment points for the maximum & minimum values.

Technical Attributes.

Output square drive outside (inch)	1/2"
Width mm (b)	55 mm
Size	10
Size hexagon socket [internal square]	9 x 12 mm
Height mm (h)	55 mm
Length mm (L)	430 mm
Measuring range N·m	20-100 N·m

Logistics data.

Length (IFS)	430
Width (IFS)	55
Height (IFS)	55
Length (packed, mm)	430
Width (packed, mm)	55
Height (packed, mm)	55
Volume (packed, mm)	1.30075 dm ³
Artikelnummer	96504010
Weight (gross, kg)	1,190
Weight PAP (kg)	0,000
Weight PVC (kg)	0,116
GTIN	4018754269495
Country of origin	GERMANY
Region of origin	Nordrhein-Westfalen
WEEE/Electrical Act	nicht ear-pflichtig
Customs tariff no.	82041100
Numbers of content units per order units	1

Weight

1190 g

Parts list.



50184010
Torque wrench service
MANOSKOP

Variants.

Artikelnummer	Article number (ERP)	Article description (Autom.)	GTIN
96501054	730R/2-1 Quick	Torque spanner MANOSKOP No. 730R Measuring-R. 2-10N·m Output 1/4" L. 250mm	4018754339976
96504002	730R/2 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Measuring-R. 4-20N·m Output 3/8" L. 255mm	4018754311354
96504004	730R/4 QUICK	Torque spanner MANOSKOP No. 730R Measuring-R. 8-40N·m Output 3/8" L. 285mm	4018754311361
96504005	730R/5 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Measuring-R. 6-50N·m Output 3/8" L. 380mm	4018754269488
96504010	730R/10 QUICK	Torque spanner MANOSKOP No. 730R Measuring-R. 20-100N·m Output 1/2" L. 430mm	4018754269495
96504012	730R/12 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Measuring-R. 25-130N·m Output 1/2" L. 475mm	4018754269501
96504020	730R/20 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Measuring-R. 40-200N·m Output 1/2" L. 530mm	4018754269518
96504030	730R/30 QUICK	Torque spanner MANOSKOP No. 730R Measuring-R. 60-300N·m Output 1/2" L. 590mm	4018754326006
96504040	730R/40 QUICK	Torque spanner MANOSKOP No. 730R Measuring-R. 80-400N·m Output 3/4" L. 675mm	4018754269525
96504565	730RII/65 QUICK	Torque spanner MANOSKOP No. 730R Measuring-R. 130-650N·m Output 3/4" L. 1125mm	4018754269563

GTIN-Code.



Images.

